

**Amendments to the Claims**

This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

1. (Currently Amended) A method of producing treated water comprising:  
introducing water to be treated from a point of entry into a reservoir system vessel and  
while introducing the water to be treated into an electrochemical device;  
removing at least a portion of any undesirable species from the water in the  
electrochemical device while suppressing hydroxyl ion generation to produce treated water;  
storing at least a portion of the treated water in the reservoir system vessel; and  
distributing at least a portion of the water from the reservoir system vessel to a point of  
use in a household.
1. (Canceled).
3. (Original) The method of claim 1, wherein removing the at least a portion of any  
undesirable species while suppressing hydroxyl ion generation comprises applying an electrical  
current below a limiting current density.
4. (Currently Amended) The method of claim 1, further comprising measuring at least one  
water property of at least a portion of the water in the reservoir system vessel.
5. (Original) The method of claim 4, further comprising adjusting an operating parameter of  
the electrochemical device based on the measured water property.
6. (Original) The method of claim 4, further comprising distributing at least a portion of the  
treated water to a point of use based on the measured water property.

7. (Original) The method of claim 4, further comprising adjusting a flow rate of the water into the electrochemical device based on the measured water property.

8. (Currently Amended) The method of claim 1, wherein the act of storing at least a portion of the treated water comprises storing at least a portion the treated water in a pressurized reservoir system vessel.

9. (Currently Amended) The method of claim 8, wherein storing the treated water in the pressurized reservoir system vessel comprises storing the treated water in a treated water zone of the pressurized reservoir system vessel.

10. (Original) The method of claim 1, wherein the electrochemical device comprises an electrodeionization device.

11. (Currently Amended) A method of producing treated water comprising:  
introducing water a first portion of water to be treated from a point of entry into a reservoir vessel and a second portion of the water to be treated into an electrodeionization device;  
introducing a portion of the water from the reservoir into an electrochemical vessel into the electrodeionization device;  
applying an electrical current below a limiting current density through the electrochemical electrodeionization device to promote removal of any undesirable species from the water and produce treated water; and  
maintaining the electrical current below the limiting current density to produce the treated water.

12. (Currently Amended) The method of claim 11, further comprising storing the treated water in the reservoir vessel.

13. (Currently Amended) The method of claim 12, further comprising measuring a water property of water in the ~~reservoir~~vessel.
14. (Original) The method of claim 13, wherein applying the electrical current comprises adjusting the electrical current based on the measured water property.
15. (Currently Amended) The method of claim 14, wherein introducing water from the point of entry into the ~~reservoir~~vessel comprises adjusting a water flow rate based on the measured water property.
16. (Currently Amended) The method of claim 15, further comprising distributing at least a portion of the treated water to a household point of use.
17. (Currently Amended) A water treatment system comprising:  
a ~~reservoir~~systemvessel fluidly connected to a point of entry, the ~~reservoir~~systemvessel comprising a plurality of zones having water contained therein with differing water quality levels;  
an electrochemical device fluidly connected to the point of entry and the ~~reservoir~~systemvessel;  
a power supply for providing an electrical current to the electrochemical device; and  
a controller for regulating the electrical current below a limiting current density.
18. (Currently Amended) The system of claim 17, further comprising a household distribution system fluidly connected downstream of the reservoir system and to a point of use.
19. (Original) The system of claim 17, further comprising at least one water property sensor.
20. (Original) The system of claim 19, wherein the electrochemical device comprises an electrodeionization device.

21. (Canceled).
22. (Currently Amended) A method of facilitating water treatment comprising:  
providing a pressurizable ~~reservoir system vessel~~ fluidly connectable downstream of [[to]] a point of entry and further fluidly connectable upstream of a household distribution system fluidly ~~connect~~connected to at least one point of use selected from the group consisting of a showerhead, a kitchen sink faucet, a washing machine, and a dishwasher;  
providing an electrochemical device fluidly connected downstream of the pressurizable ~~reservoir system vessel~~;  
providing a power supply for providing an electrical current to the electrochemical device; and  
providing a controller for regulating the electrical current below a limiting current density.
23. (Canceled).
24. (Canceled).
25. (Canceled).
26. (Canceled).
27. (Previously Presented) The method of claim 11, further comprising a step of providing treated water mixed with water from the point of entry.
28. (Currently Amended) The method of claim 10, further comprising measuring a plurality of water quality levels of the water in the ~~reservoir system vessel~~.

29. (Currently Amended) The system of claim 17, wherein at least a portion of the ~~reservoir~~  
~~systemvessel~~ is pressurized.

30. (Previously Presented) The system of claim 29, wherein the controller is further  
configured to regulate delivery of water from at least one of the zones to at least one point of use.

31. (Previously Presented) The system of claim 17, wherein the controller is further  
configured to receive at least one signal representative of at least one water quality level of at  
least one zone and regulate the electrical current based at least partially on the at least one signal.

32. (Currently Amended) The method of claim 22, further comprising a step of connecting  
the controller to at least one water property sensor disposed in the pressurizable ~~reservoir~~  
~~systemvessel~~.